Technical Data Sheet

9/9/19 Version 1.6

Description

CRS primer has the ability to create a strong adhesive bond with metal and provide a surface coating that encapsulates corrosion and protects old, deteriorating, ferrous substrates. CRS may be applied directly to surfaces with tightly adhered intact rust (with proper preparation). CRS will penetrate tightly adhered intact rust to bond with the metal substrate below to stop the corrosion process.

When properly applied, CRS provides both the applicator and asset owner with a cost effective infrastructure maintenance program. CRS is environmentally friendly due to it being water-based, extremely low VOC level, and ease of application and use.

NOTE: Maxon CRS is not a structural or restorative product and should only be used on substrates that are structurally sound.

MADE IN THE USA

Basic Usage

CRS is primarily used as a primer coating to protect ferrous materials from further deterioration and loss of mass, through exposure to many naturally occurring elements.

- Concrete encased metal
- Metal Stairs and Ramps
- Corrosion Under Insulation (CUI)
- Corrugated and Metal Roofs

- Ship Decks
- Columns Beams Bridges
- Tanks
- Mines, Infrastructure, Pipe exteriors

CRS, in some cases may be used in some cases as a stand-alone solution, although more often as a part of a more comprehensive solution utilizing other Maxon Technologies' products. In addition, CRS may be used as a functional primer for other coating systems.

Benefits

- Simplified surface preparation
- Can be applied via brush, spray, or roll
- Penetrates rust and bonds to metal below
- Extends time between maintenance cycles
- 1K Water-borne product

- Flexible re-coat window (weeks vs hours)
- Ease of clean-up (water and solvents)
- Remarkable ease of application
- Minimal odor
- Water resistant

MADE IN THE USA



5400 W. Rosecrans Ave Hawthorne, CA 90250 (424) 236-4660

9/9/19 Version 1.6

Information / Composition of Components

Proprietary formulation no hazardous ingredients according to the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Number of Components:	One	
Mass Density:	1.2-1.3 gr/cc	
Volume Solids:	52% ±2%	
VOC:	Under 1.0	
Viscosity:	200-600 cSt	
pH:	8-9	
Recommended DFT:	1-3 mils Dry Film Thickness (DFT)	
Time Dry to Touch:	20-40min.	
Overcoating Intervals:	When dry to touch	
Full Cure After:	24-48 hours	
Shelf Life:	24 months at 4-40 Degrees Celsius	
	(in original sealed container)	
Physical State at 20 ⁰ C:	Liquid	
Appearance:	Milky White, White, Yellow, Colors	
Odor:	Slight Acrylic	
Freezing Point [^O C]:	0 ^o C	
Boiling Point [^O C]:	100 ⁰ C	
Vapor Pressure:	2.3 kPa at RT	
Flammability (Solid, Gas):	Not Flammable	

MADE IN THE USA



5400 W. Rosecrans Ave Hawthorne, CA 90250 (424) 236-4660

Upper / Lower Limit on Flammability or Explosive Limits

Flammability Limit Upper (%):	N/A
-------------------------------	-----

Flammability Limit Lower (%): N/A

Solubility in Water: Partial

Auto-ignition Temperature [^OC]: N/A

Decomposition point [^OC]: N/A

Dry / Cure Time Guidelines for CRS		
Substrate Temperature	Time - Dry to Touch	Time - Dry to Service (Chemical Cure)
21°C / 70°F	1 hour	48 hours
32°C / 90°F	45 minutes	24 hours

MADE IN THE USA

Refer to our Material Safety Data Sheet (MSDS) regarding regulatory compliance, safety, hazards, spill procedures and disposal of this product.

While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. Because many factors may affect processing or application/ use, we recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE.



5400 W. Rosecrans Ave Hawthorne, CA 90250 (424) 236-4660